

Printing date 12.06.2015 V-1 Revision: 12.06.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

Trade name: CLEANER SLOW (SOLVENT BASED)

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses: professional use.

Application of the substance / the mixture Degreasing agent

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Chemical Alliance Polska Sp. z o.o.

ul. Prosta 23, Łozienica

72-100 Goleniów

Tel. +48 91 41 65 440

Fax: +48 91 41 65 487

info@cap.pl

Further information obtainable from: sds@cap.pl

1.4 Emergency telephone number: +48 91 41 65 440 (8:00-16:00)

## SECTION 2: Hazards identification

## 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



Asp. Tox. 1 H304 May be f

H304 May be fatal if swallowed and enters airways.



STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## Hazard pictograms







GHS02

GHS07

GHS08

## Signal word Danger

## Hazard-determining components of labelling:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

## Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

 $H412\ Harmful\ to\ aquatic\ life\ with\ long\ lasting\ effects.$ 

## Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Printing date 12.06.2015 V- 1 Revision: 12.06.2015

## Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 1)

*P261* Avoid breathing mist/vapours/spray.

*Use only outdoors or in a well-ventilated area.* 

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

*P331* Do NOT induce vomiting.

*P501* Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

#### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics  Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	50-100%
	hydrocarbons, C9, aromatics  Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411;  STOT SE 3, H335-H336	2.5-10%
	reaction mass of ethylbenzene and m-xylene and p-xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%

**Additional information:** For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

## 4.1 Description of first aid measures

#### General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

## After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# SECTION 5: Firefighting measures

## 5.1 Extinguishing media

Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)



Printing date 12.06.2015 V-1 Revision: 12.06.2015

Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 2)

#### 5.3 Advice for firefighters

## Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

#### Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

#### 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

## Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

Fumes can combine with air to form an explosive mixture.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

#### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.



Printing date 12.06.2015 V- 1 Revision: 12.06.2015

Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 3)

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
reaction mass of ethylbenzene and m-xylene and p-xylene		
WEL (Great Britain	) Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk, BMGV	
DNELs		
hydrocarbons, C9, aromatics		
Dermal DNEL 2	25 mg/kg bw/day (long-term - systemic effects, workers)	
Inhalative DNEL	150 mg/m3 (long-term - systemic effects, workers)	
Ingredients with biological limit values:		
reaction mass of ethylbenzene and m-xylene and p-xylene		
BMGV (Great Britain) 650 mmol/mol creatinine		
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	

Additional information: The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Do not eat or drink while working.

## Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

### Protection of hands:

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).


## Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## Eye protection:



**Body protection:** Protective work clothing



Printing date 12.06.2015 V- 1 Revision: 12.06.2015

Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 4)

SECTION 9: 1	Pnysicai ana	cnemicai	properiies

9.1 Information on basic physical a	and chemical properties
General Information	c
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137 °C
	Undetermined.
Flash point:	32 °C
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20 °C:	8 hPa
Density:	0.74-0.79 g/cm³
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

## SECTION 10: Stability and reactivity

9.2 Other information

- 10.1 Reactivity No decomposition if used according to specifications.
- 10.2 Chemical stability No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions Fumes can combine with air to form an explosive mixture.
- 10.4 Conditions to avoid Protect from heat and direct sunlight.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

(Contd. on page 6)



Printing date 12.06.2015 V- 1 Revision: 12.06.2015

Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 5)

## SECTION 11: Toxicological information

# 11.1 Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:			
hydrocarbo	hydrocarbons, C9, aromatics		
Oral	LD50	3592 mg/kg (rat)	
Dermal	LD50	>3160 mg/kg (-)	
Inhalative	LC50/4 h	> 6193 mg/l (rat)	
reaction m	reaction mass of ethylbenzene and m-xylene and p-xylene		
Oral	ATE	>2000 mg/kg (-)	
Dermal	ATE	1466.67 mg/kg (-)	
Inhalative	ATE	12.09 mg/l (-)	

#### Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

## 12.1 Toxicity

Aquatic toxicity:	
hydrocarbons, C9, aromatics	
EC50/10 min	>99 mg/l (microorganisms)
EC50/48 h	6.14 mg/l (Daphnia magna)
EL50/48 h	3.2 mg/l (Daphnia magna)
ErC50/96 h	9.2 mg/l (fish)
ErL50/72 h	2.9 mg/l (Pseudokirchnerella subcapitata)

## 12.2 Persistence and degradability

#### hydrocarbons, C9, aromatics

Biodegradation 78 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.



Printing date 12.06.2015 V- 1 Revision: 12.06.2015

Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 6)

12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant (IMDG):	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler): EMS Number:	30 F-E,S-E
14.7 Transport in bulk according to Annex II of and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3 D/E
IMDG	5.5
IMDG Limited quantities (LQ)	5L
UN "Model Regulation":	UN1263, PAINT RELATED MATERIAL, 3, III

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



Printing date 12.06.2015 V-1 Revision: 12.06.2015

Trade name: CLEANER SLOW (SOLVENT BASED)

(Contd. of page 7)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

#### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources European Chemicals Agency, http://echa.europa.eu/