

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** ELASTIC ADDITIVE

**1.2 Relevant identified uses of the substance or mixture and uses advised against** Identified uses: professional use.  
Application of the substance / the mixture Flexibilitating additive

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

Chemical Alliance Polska Sp. z o.o.

ul. Prosta 23, Łozienica

72-100 Goleniów

Tel. +48 91 41 65 440

Fax: +48 91 41 65 487

info@cap.pl

**Further information obtainable from:** sds@cap.pl

**1.4 Emergency telephone number:** +48 91 41 65 440 (8:00-16:00)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02



GHS07

**Signal word** Warning

**Hazard-determining components of labelling:**

n-butyl acetate

**Hazard statements**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: Use for extinction: ABC powder.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

**Trade name: ELASTIC ADDITIVE**

(Contd. of page 1)

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-50%
---	-----------------	---	--------

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

**After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** Extinguishing powder. Do not use water.**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

**5.3 Advice for firefighters****Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 3)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

**Trade name: ELASTIC ADDITIVE**

(Contd. of page 2)

Keep away from ignition sources.

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

Dispose of the material collected according to regulations.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

#### 7.2 Conditions for safe storage, including any incompatibilities

**Storage:**

**Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.

**Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

#### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

**123-86-4 n-butyl acetate**

WEL (Great Britain)	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
---------------------	---

**Regulatory information** WEL (Great Britain): EH40/2011

**DNELs**

**123-86-4 n-butyl acetate**

Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m <sup>3</sup> (acute - systemic effects, workers) 960 mg/m <sup>3</sup> (acute - local effects, workers) 480 mg/m <sup>3</sup> (long-term - systemic effects, workers) 480 mg/m <sup>3</sup> (long-term - local effects, workers)

**PNECs**

**123-86-4 n-butyl acetate**

PNEC	0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases)
------	--

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

**Trade name: ELASTIC ADDITIVE**

(Contd. of page 3)

PNEC	35.6 mg/l (sewage treatment plants) 0.981 mg/kg (freshwater sediment environment)
------	--

**Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

#### Respiratory protection:

Filter A2/P2

Use suitable respiratory protective device in case of insufficient ventilation.

#### Protection of hands:



Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

#### Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

PVA gloves

Recommended thickness of the material:  $\geq 0,7$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Value for the permeation: Level 6  $\geq 480$  min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:



Tightly sealed goggles

**Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Appearance:

<b>Form:</b>	Fluid
<b>Colour:</b>	Colourless/ slightly yellow
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not applicable.

(Contd. on page 5)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

**Trade name: ELASTIC ADDITIVE**

(Contd. of page 4)

<b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	124-128 °C Undetermined.
<b>Flash point:</b>	24 °C
<b>Flammability (solid, gas):</b>	Not applicable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto-ignition temperature:</b>	Not determined.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Explosion limits:</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	15 Vol %
<b>Vapour pressure at 20 °C:</b>	10.7 hPa
<b>Density at 20 °C:</b>	1.06 g/cm <sup>3</sup>
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Partition coefficient: n-octanol/water:</b>	Not determined.
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
<b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No decomposition if used according to specifications.

**10.2 Chemical stability** No decomposition if used and stored according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

**10.4 Conditions to avoid** Protect from heat and direct sunlight.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**123-86-4 n-butyl acetate**

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)

(Contd. on page 6)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

**Trade name: ELASTIC ADDITIVE**

(Contd. of page 5)

**Primary irritant effect:**
**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

**12.1 Toxicity**
**Aquatic toxicity:**
**123-86-4 n-butyl acetate**

LC50/96 h 18 mg/l (Pimephales promelas)

TT/16 h 115 mg/l (Pseudomonas putida)

EC50/48 h 44 mg/l (daphnia)

EC50/72 h 675 mg/l (algae)

**12.2 Persistence and degradability**
**123-86-4 n-butyl acetate**

Biodegradation 83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)

**12.3 Bioaccumulative potential**
**123-86-4 n-butyl acetate**

BCF 15.3 (-)

log Pow 2.3

**12.4 Mobility in soil**
**123-86-4 n-butyl acetate**

log Koc 1.27

**Additional ecological information:**
**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**
**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**
**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

**Uncleaned packaging:**
**Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.05.2018


V- 1.0

Revision: 25.05.2018

Trade name: ELASTIC ADDITIVE

(Contd. of page 6)

### SECTION 14: Transport information

<b>14.1 UN-Number</b> <b>ADR, IMDG, IATA</b>	UN1263
<b>14.2 UN proper shipping name</b> <b>ADR</b> <b>IMDG, IATA</b>	1263 PAINT RELATED MATERIAL solution PAINT RELATED MATERIAL solution
<b>14.3 Transport hazard class(es)</b> <b>ADR, IMDG, IATA</b>	 <div> Class 3  Label 3 </div>
<b>14.4 Packing group</b> <b>ADR, IMDG, IATA</b>	III
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>14.6 Special precautions for user</b> <b>Danger code (Kemler):</b> <b>EMS Number:</b> <b>Stowage Category</b>	Warning: Flammable liquids. 30 F-E, <u>S</u> -E A
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b> <b>Limited quantities (LQ)</b> <b>Transport category</b> <b>Tunnel restriction code</b>	5L 3 D/E
<b>IMDG</b> <b>Limited quantities (LQ)</b>	5L
<b>UN "Model Regulation":</b>	UN 1263 PAINT RELATED MATERIAL SOLUTION, 3, III

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 25.05.2018

V- 1.0

Revision: 25.05.2018

---

**Trade name: ELASTIC ADDITIVE**

---

(Contd. of page 7)

---

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

**Relevant phrases**

*H226 Flammable liquid and vapour.*

*H336 May cause drowsiness or dizziness.*

**Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 3: Flammable liquids – Category 3*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

**Sources** European Chemicals Agency, <http://echa.europa.eu/>