

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 6:1 WET ON WET FILLER PLUS

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses: professional use.
Application of the substance / the mixture Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Chemical Alliance Polska Sp. z o.o.

ul. Prosta 23, Łozienica

72-100 Goleniów

Tel. +48 91 41 65 440

info@cap.pl

Further information obtainable from: sds@cap.pl

1.4 Emergency telephone number: +48 91 41 65 440 (8:00-16:00)

*** SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Warning

Hazard-determining components of labelling:

xylene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 1)

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

* SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
List no.: 905-562-9 Reg.nr.: 01-2119555267-33	Reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5- <10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1-5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-5%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1-5%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1- <2.5%
CAS: 110-43-0 EINECS: 203-767-1 Reg.nr.: 01-2119902391-49	heptan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H336	1-5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-butoxyethyl acetate ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332	1-5%
List no.: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	1- <2.5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.25- <1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 2)

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

*** SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

*** SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

Dispose of the material collected according to regulations.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 3)

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

* SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
---------------------	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 4)

100-41-4 ethylbenzene	
WEL (Great Britain)	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
IOELV (EU)	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin
110-43-0 heptan-2-one	
WEL (Great Britain)	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 238 mg/m ³ , 50 ppm Skin
112-07-2 2-butoxyethyl acetate	
WEL (Great Britain)	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
IOELV (EU)	Short-term value: 333 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Skin

Regulatory information

WEL (Great Britain): EH40/2011

IOELV (EU): (EU) 2017/164

DNELs		
Reaction mass of ethylbenzene and m-xylene and p-xylene		
Dermal	DNEL	212 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	442 mg/m ³ (acute - systemic effects, workers) 442 mg/m ³ (acute - local effects, workers) 221 mg/m ³ (long-term - systemic effects, workers) 221 mg/m ³ (long-term - local effects, workers)
1330-20-7 xylene		
Dermal	DNEL	180 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	289 mg/m ³ (acute - systemic effects, workers)
123-86-4 n-butyl acetate		
Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) 480 mg/m ³ (long-term - local effects, workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	DNEL	153.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	275 mg/m ³ (long-term - systemic effects, workers)
7779-90-0 trizinc bis(orthophosphate)		
Dermal	DNEL	83 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1 mg/m ³ (long-term - systemic effects, workers)
110-43-0 heptan-2-one		
Dermal	DNEL	54.27 mg/kg bw/day (long-term - systemic effects, workers)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 5)

Inhalative	DNEL	1,516 mg/m ³ (acute - systemic effects, workers) 394.25 mg/m ³ (long-term - systemic effects, workers)
112-07-2 2-butoxyethyl acetate		
Dermal	DNEL	102 mg/kg bw/day (acute - systemic effects, workers) 102 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	775 mg/m ³ (acute - systemic effects, workers) 333 mg/m ³ (acute - local effects, workers) 133 mg/m ³ (long-term - local effects, workers)
hydrocarbons, C9, aromatics		
Dermal	DNEL	25 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	150 mg/m ³ (long-term - systemic effects, workers)
1314-13-2 zinc oxide		
Dermal	DNEL	83 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	5 mg/m ³ (long-term - systemic effects, workers)
PNECs		
Reaction mass of ethylbenzene and m-xylene and p-xylene		
PNEC		6.58 mg/l (sewage treatment plants)
PNEC		12.46 mg/kg (freshwater sediment environment) 12.46 mg/kg (marine sediment environment)
PNEC		327 µg/l (freshwater environment) 327 µg/l (marine environment) 327 µg/l (intermittent releases)
1330-20-7 xylene		
PNEC		0.327 mg/l (freshwater environment) 0.327 mg/l (marine environment)
PNEC		12.46 mg/kg (freshwater sediment environment) 12.46 mg/kg (marine sediment environment)
123-86-4 n-butyl acetate		
PNEC		0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases) 35.6 mg/l (sewage treatment plants)
PNEC		0.981 mg/kg (freshwater sediment environment)
108-65-6 2-methoxy-1-methylethyl acetate		
PNEC		0.635 mg/l (freshwater environment) 0.0635 mg/l (marine environment) 6.35 mg/l (intermittent releases) 100 mg/l (sewage treatment plants)
PNEC		3.29 mg/kg (freshwater sediment environment) 0.329 mg/kg (marine sediment environment)
7779-90-0 trizinc bis(orthophosphate)		
PNEC		235.6 mg/kg (freshwater sediment environment) 113 mg/kg (marine sediment environment)
110-43-0 heptan-2-one		
PNEC		0.0982 mg/l (freshwater environment) 0.00982 mg/l (marine environment)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 6)

PNEC	0.982 mg/l (intermittent releases)
	12.5 mg/l (sewage treatment plants)
	1.89 mg/kg (freshwater sediment environment)
	0.189 mg/kg (marine sediment environment)
	0.321 mg/kg (soil)
112-07-2 2-butoxyethyl acetate	
PNEC	0.304 mg/l (freshwater environment)
	0.0304 mg/l (marine environment)
	0.56 mg/l (intermittent releases)
	90 mg/l (sewage treatment plants)
	2.03 mg/kg (freshwater sediment environment)
PNEC	0.203 mg/kg (marine sediment environment)
	0.68 mg/kg (soil)
1314-13-2 zinc oxide	
PNEC	0.0206 mg/l (freshwater environment)
	0.0061 mg/l (marine environment)
	0.1 mg/l (sewage treatment plants)
PNEC	117.8 mg/kg (freshwater sediment environment)
	56.5 mg/kg (marine sediment environment)
	35.6 mg/kg (soil)
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Regulatory information BMGV (Great Britain): EH40/2011

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P2

Protection of hands:



Protective gloves

Check the permeability prior to each renewed use of the glove.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 7)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:


Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information
Appearance:

Form:	Fluid
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

Flash point: >23 °C

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	0.7 Vol %
Upper:	15 Vol %

Vapour pressure at 20 °C: 10.7 hPa

Density:	1.43-1.47 g/cm ³
Vapour density	Not determined.
Evaporation rate	Not determined.

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic at 20 °C: 250 mPas

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 8)

Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No decomposition if used according to specifications.
10.2 Chemical stability No decomposition if used and stored according to specifications.
10.3 Possibility of hazardous reactions
 Reacts with alkali, amines and strong acids.
 Reacts with oxidising agents.
 Fumes can combine with air to form an explosive mixture.
10.4 Conditions to avoid Protect from heat and direct sunlight.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products:
 Carbon monoxide and carbon dioxide
 Formation of toxic gases is possible during heating or in case of fire.

* SECTION 11: Toxicological information

11.1 Information on toxicological effects
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Reaction mass of ethylbenzene and m-xylene and p-xylene

Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

1330-20-7 xylene

Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/6 h	4,345 mg/l (rat)

100-41-4 ethylbenzene

Inhalative	LC50/4 h	11 mg/l (ATE)
------------	----------	---------------

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

110-43-0 heptan-2-one

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>16.7 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral	LD50	1,880 mg/kg (rat)
Dermal	LD50	1,500 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 9)

hydrocarbons, C9, aromatics		
Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg
Inhalative	LC50/4 h	>6,193 mg/l (rat)
1314-13-2 zinc oxide		
Oral	LD50	>5,000 mg/kg (rat)

Primary irritant effect:
Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

*** SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity:
Reaction mass of ethylbenzene and m-xylene and p-xylene

LC50/72 h 2.6-8.4 mg/l (fish)

LC50/96h 3,300-4,093 µg/l (Oncorhynchus mykiss)

1330-20-7 xylene

LC50/96 h 2.6 mg/l (Oncorhynchus mykiss) (OECD 203)

EC50/3 h >157 mg/l (microorganisms)

EC50/48 h >3.4 mg/l (Ceriodaphnia dubia) (OECD 202)

EC50/73h 2.2 mg/l (Pseudokirchnerella subcapitata) (OECD 201)

123-86-4 n-butyl acetate

LC50/96 h 18 mg/l (Pimephales promelas)

TT/16 h 115 mg/l (Pseudomonas putida)

EC50/48 h 44 mg/l (daphnia)

EC50/72 h 675 mg/l (algae)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96 h >100 mg/l (fish)

EC50/48 h >500 mg/l (Daphnia magna)

EC20/30 min >1,000 mg/l (microorganisms)

EC50/72 h >1,000 mg/l (Pseudokirchnerella subcapitata)

EC50 >100 mg/l (Pseudokirchnerella subcapitata)

>100 mg/l (Pimephales promelas)

>100 mg/l (Daphnia magna)

7779-90-0 trizinc bis(orthophosphate)

EC50/3 h 5.2 mg/l (microorganisms)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 10)

EC50/48 h	>2.34 mg/l (<i>Daphnia magna</i>)
110-43-0 heptan-2-one	
LC50/96 h	131 mg/l (<i>Pimephales promelas</i>)
EC50/72 h	98.2 mg/l (<i>Pseudokirchnerella subcapitata</i>)
112-07-2 2-butoxyethyl acetate	
EC50/72 h	>100 mg/l (<i>Scenedesmus subspicatus</i>)
EC50/24 h	>100 mg/l (<i>Daphnia magna</i>)
LC50/48 h	10-100 mg/l (<i>Leuciscus idus melanotus</i>)
hydrocarbons, C9, aromatics	
ErC50/96 h	9.2 mg/l (fish)
EL50/48 h	3.2 mg/l (<i>Daphnia magna</i>)
ErL50/72 h	2.9 mg/l (<i>Pseudokirchnerella subcapitata</i>)
EC50/48 h	6.14 mg/l (<i>Daphnia magna</i>)
EC50/10 min	>99 mg/l (microorganisms)
1314-13-2 zinc oxide	
LC50/96 h	4.92 mg/l (fish)
EC50/72 h	0.042 mg/l (<i>Pseudokirchnerella subcapitata</i>)
EC50/24 h	9.4 mg/l (microorganisms)
LC50/48 h	1.55 mg/l (<i>Daphnia magna</i>)
12.2 Persistence and degradability	
Reaction mass of ethylbenzene and m-xylene and p-xylene	
Biodegradation	75 % (readily biodegradable)
1330-20-7 xylene	
Biodegradation	>60 % (readily biodegradable)
123-86-4 n-butyl acetate	
Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
108-65-6 2-methoxy-1-methylethyl acetate	
Biodegradation	100 % (readily biodegradable) (OECD 302 B, 8 d, aerobic)
110-43-0 heptan-2-one	
Biodegradation	69 % (readily biodegradable) (OECD 310, 28 d, aerobic)
112-07-2 2-butoxyethyl acetate	
Biodegradation	>70 % (readily biodegradable) (OECD 301C, 28d)
hydrocarbons, C9, aromatics	
Biodegradation	78 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
12.3 Bioaccumulative potential	
1330-20-7 xylene	
BCF	25.9
log K _{ow}	<3.2
123-86-4 n-butyl acetate	
BCF	15.3 (-)
log P _{ow}	2.3
108-65-6 2-methoxy-1-methylethyl acetate	
log P _{ow}	0.56
12.4 Mobility in soil	
123-86-4 n-butyl acetate	
log K _{oc}	1.27

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 11)

108-65-6 2-methoxy-1-methylethyl acetate	
Koc	1.7

Additional ecological information:
General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations


13.1 Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es) ADR, IMDG, IATA	<div style="text-align: center;">  </div> <div> Class 3 Label 3 </div>
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant (IMDG):	Not applicable. Yes
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 12)

Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT, 3, III

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/eye irritation Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.07.2018

V- 2.0

Revision: 16.07.2018

Trade name: 6:1 WET ON WET FILLER PLUS

(Contd. of page 13)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources European Chemicals Agency, <http://echa.europa.eu/>

*** Data compared to the previous version altered.**