

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** *MULTI LIGHT PUTTY*

**1.2 Relevant identified uses of the substance or mixture and uses advised against** *Identified uses: professional use.*

**Application of the substance / the mixture** *Knife filler/ Surfacers*

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

*Chemical Alliance Polska Sp. z o.o.*

*ul. Prosta 23, Łozienica*

*72-100 Goleniów*

*Tel. +48 91 41 65 440*

*info@cap.pl*

**Further information obtainable from:** *sds@cap.pl*

**1.4 Emergency telephone number:** *+48 91 41 65 440 (8:00-16:00)*

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**



GHS02

*Flam. Liq. 3 H226 Flammable liquid and vapour.*



GHS08

*Repr. 2 H361d Suspected of damaging the unborn child.*

*STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.*



GHS07

*Skin Irrit. 2 H315 Causes skin irritation.*

*Eye Irrit. 2 H319 Causes serious eye irritation.*

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

*The product is classified and labelled according to the CLP regulation.*

**Hazard pictograms**



GHS02



GHS07



GHS08

**Signal word** *Danger*

**Hazard-determining components of labelling:**

*styrene*

**Hazard statements**

*H226 Flammable liquid and vapour.*

*H315 Causes skin irritation.*

*H319 Causes serious eye irritation.*

*H361d Suspected of damaging the unborn child.*

*H372 Causes damage to the hearing organs through prolonged or repeated exposure.*

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 1)

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## \* SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

<b>Dangerous components:</b>		
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	10-<20%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	0.1-<1%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-<1%
CAS: 2687-91-4 EINECS: 220-250-6 Reg.nr.: 01-2119472138-36	N-Ethyl-2-Pyrrolidone Repr. 1B, H360D; Eye Dam. 1, H318	0.1-<0.3%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

#### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

---

**Trade name: MULTI LIGHT PUTTY**

---

(Contd. of page 2)

---

**SECTION 5: Firefighting measures**

---

**5.1 Extinguishing media****Suitable extinguishing agents:***CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.***For safety reasons unsuitable extinguishing agents:** *Water with full jet***5.2 Special hazards arising from the substance or mixture***Can form explosive gas-air mixtures.**Formation of toxic gases is possible during heating or in case of fire.***5.3 Advice for firefighters****Protective equipment:***Wear self-contained respiratory protective device.**Do not inhale explosion gases or combustion gases.***Additional information***Cool endangered receptacles with water spray.**Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.**Collect contaminated fire fighting water separately. It must not enter the sewage system.*

---

**SECTION 6: Accidental release measures**

---

**6.1 Personal precautions, protective equipment and emergency procedures***Mount respiratory protective device.**Wear protective equipment. Keep unprotected persons away.**Ensure adequate ventilation**Keep away from ignition sources.**Avoid contact with the eyes and skin.***6.2 Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.***6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Do not flush with water or aqueous cleansing agents.**Dispose of the material collected according to regulations.***6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.*

---

**SECTION 7: Handling and storage**

---

**7.1 Precautions for safe handling***Ensure good ventilation/exhaustion at the workplace.**Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).**Do not inhale gases / fumes / aerosols.**Avoid contact with the eyes and skin.**Do not eat, drink, smoke or sniff while working.**Do not allow to enter sewers/ surface or ground water.***Information about fire - and explosion protection:***Keep ignition sources away - Do not smoke.**Keep respiratory protective device available.**Fumes can combine with air to form an explosive mixture.***7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** *Store only in the original receptacle.***Information about storage in one common storage facility:***Store away from foodstuffs.**Store away from oxidising agents.*

---

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 3)

**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

**7.3 Specific end use(s)** No further relevant information available.

### \* SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**
**Ingredients with limit values that require monitoring at the workplace:**
**100-42-5 styrene**

WEL (Great Britain)	Short-term value: 1080 mg/m <sup>3</sup> , 250 ppm Long-term value: 430 mg/m <sup>3</sup> , 100 ppm
---------------------	--

**141-78-6 ethyl acetate**

WEL (Great Britain)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
IOELV (EU)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm

**111-76-2 2-butoxyethanol**

WEL (Great Britain)	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 123 mg/m <sup>3</sup> , 25 ppm Sk, BMGV
IOELV (EU)	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 98 mg/m <sup>3</sup> , 20 ppm Skin

**Regulatory information**

WEL (Great Britain): EH40/2018

IOELV (EU): (EU) 2017/164

**DNELs**
**100-42-5 styrene**

Dermal	DNEL	406 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	289 mg/m <sup>3</sup> (acute - systemic effects, workers) 306 mg/m <sup>3</sup> (acute - local effects, workers) 85 mg/m <sup>3</sup> (long-term - systemic effects, workers)

**141-78-6 ethyl acetate**

Dermal	DNEL	63 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1,468 mg/m <sup>3</sup> (acute - systemic effects, workers) 1,468 mg/m <sup>3</sup> (acute - local effects, workers) 734 mg/m <sup>3</sup> (long-term - systemic effects, workers) 734 mg/m <sup>3</sup> (long-term - local effects, workers)

**111-76-2 2-butoxyethanol**

Dermal	DNEL	89 mg/kg bw/day (acute - systemic effects, workers) 125 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1,091 mg/m <sup>3</sup> (acute - systemic effects, workers) 246 mg/m <sup>3</sup> (acute - local effects, workers) 98 mg/m <sup>3</sup> (long-term - systemic effects, workers)

**PNECs**
**100-42-5 styrene**

PNEC	0.028 mg/l (freshwater environment)
------	-------------------------------------

(Contd. on page 5)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 4)

PNEC	0.0028 mg/l (marine environment)
	0.04 mg/l (intermittent releases)
	5 mg/l (sewage treatment plants)
	0.614 mg/kg (freshwater sediment environment)
	0.0614 mg/kg (marine sediment environment)
	0.2 mg/kg (soil)
<b>141-78-6 ethyl acetate</b>	
PNEC	0.24 mg/l (freshwater environment)
	0.024 mg/l (marine environment)
	1.65 mg/l (intermittent releases)
	650 mg/l (sewage treatment plants)
PNEC	1.15 mg/kg (freshwater sediment environment)
	0.115 mg/kg (marine sediment environment)
<b>111-76-2 2-butoxyethanol</b>	
PNEC	8.8 mg/l (freshwater environment)
	0.88 mg/l (marine environment)
	9.1 mg/l (intermittent releases)
	463 mg/l (sewage treatment plants)
PNEC	3.46 mg/kg (marine environment)
	34.6 mg/kg (freshwater sediment environment)
	3.13 mg/kg (soil)
<b>Ingredients with biological limit values:</b>	
<b>111-76-2 2-butoxyethanol</b>	
BMGV (Great Britain)	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid

**Regulatory information** BMGV (Great Britain): EH40/2011

**Additional information:** The lists valid during the making were used as basis.

## 8.2 Exposure controls

### Personal protective equipment:

#### General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P2

### Protection of hands:



Protective gloves

(Contd. on page 6)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 5)

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

**Material of gloves**

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0,7$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

Value for the permeation: Level 6  $\geq 480$  min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

**Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

**Appearance:**

<b>Form:</b>	Pasty
<b>Colour:</b>	White
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not applicable.

#### Change in condition

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	145 °C

**Flash point:** 31 °C

**Flammability (solid, gas):** Not applicable.

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Not determined.

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### Explosion limits:

<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	6.1 Vol %

**Vapour pressure at 20 °C:** 6.7 hPa

**Density at 20 °C:** 1.25 g/cm<sup>3</sup>

**Vapour density:** Not determined.

**Evaporation rate:** Not determined.

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:** Not determined.

(Contd. on page 7)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 6)

**Viscosity:**
**Dynamic:**

Not determined.

**Kinematic:**

Not determined.

**9.2 Other information**

No further relevant information available.

## SECTION 10: Stability and reactivity

**10.1 Reactivity**

No decomposition if used according to specifications.

No further relevant information available.

**10.2 Chemical stability** No decomposition if used and stored according to specifications.

**10.3 Possibility of hazardous reactions**

Exothermic polymerisation.

Reacts with peroxides and other radical forming substances.

Fumes can combine with air to form an explosive mixture.

**10.4 Conditions to avoid** Protect from heat and direct sunlight.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

## SECTION 11: Toxicological information

**11.1 Information on toxicological effects**
**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**
**100-42-5 styrene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)

**141-78-6 ethyl acetate**

Oral	LD50	6,100 mg/kg (rat)
Dermal	LD50	>20,000 mg/kg (rabbit)
Inhalative	LC50/6 h	58 mg/l (rat)

**111-76-2 2-butoxyethanol**

Oral	LD50	1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)

**Primary irritant effect:**
**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Suspected of damaging the unborn child.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 8)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 7)

**Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Aquatic toxicity:

##### 100-42-5 styrene

LC50/96 h	4.02 mg/l ( <i>Pimephales promelas</i> )
EC50/48 h	4.7 mg/l ( <i>Daphnia magna</i> )
EC50/72 h	4.9 mg/l ( <i>Pseudokirchnerella subcapitata</i> )

##### 141-78-6 ethyl acetate

LC50/96 h	230 mg/l ( <i>Pimephales promelas</i> )
EC50/48 h	165 mg/l ( <i>Daphnia cucullata</i> )
EC50/72 h	>900 mg/l ( <i>Scenedesmus subspicatus</i> )
EC3/16 h	650 mg/l ( <i>Pseudomonas putida</i> )

##### 111-76-2 2-butoxyethanol

LC50/96 h	1,474 mg/l (fish)
TT/16 h	700 mg/l ( <i>Pseudomonas putida</i> )
EC50/48 h	1,550 mg/l ( <i>Daphnia magna</i> )
EC50/72 h	911 mg/l ( <i>Pseudokirchnerella subcapitata</i> )

#### 12.2 Persistence and degradability

##### 100-42-5 styrene

Biodegradation	70.9 % (readily biodegradable) (ISO 9408, 28 d, aerobic)
----------------	--

##### 141-78-6 ethyl acetate

Biodegradation	93.9 % (readily biodegradable) (OECD 301 B, aerobic)
----------------	--

##### 111-76-2 2-butoxyethanol

Biodegradation	90.4 % (readily biodegradable) (OECD 301 B, 28 d, aerobic)
----------------	--

#### 12.3 Bioaccumulative potential

##### 100-42-5 styrene

BCF	74 (-)
log Pow	2.96

##### 141-78-6 ethyl acetate

BCF	30 (-)
log Pow	0.66

#### 12.4 Mobility in soil

##### 100-42-5 styrene

log K <sub>oc</sub>	2.55
K <sub>oc</sub>	352

#### Additional ecological information:

##### General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

##### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

Trade name: **MULTI LIGHT PUTTY**

(Contd. of page 8)

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

##### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

#### 14.1 UN-Number

ADR, IMDG, IATA

UN1866

#### 14.2 UN proper shipping name

ADR

1866 RESIN SOLUTION

IMDG, IATA

RESIN SOLUTION

#### 14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3

Label

3

#### 14.4 Packing group

ADR, IMDG, IATA

III

#### 14.5 Environmental hazards:

Not applicable.

Marine pollutant (IMDG):

No

#### 14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

30

EMS Number:

F-E, S-E

Stowage Category

A

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

#### Transport/Additional information:

##### ADR

Limited quantities (LQ)

5L

Transport category

3

Tunnel restriction code

D/E

Remarks:

ADR 2.2.3.1.5

##### IMDG

Limited quantities (LQ)

5L

Remarks:

IMDG 2.3.2.5

#### UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

(Contd. on page 10)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

**Trade name: MULTI LIGHT PUTTY**

(Contd. of page 9)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category P5c** FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

##### National regulations:

##### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

##### Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360D May damage the unborn child.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

##### Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/eye irritation Reproductive toxicity Specific target organ toxicity (repeated exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

##### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.07.2019

V- 3.0

Revision: 24.07.2019

---

**Trade name: MULTI LIGHT PUTTY**

---

(Contd. of page 10)

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Repr. 1B: Reproductive toxicity. Hazard Category 1B*

*Repr. 2: Reproductive toxicity. Hazard Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**Sources** European Chemicals Agency, <http://echa.europa.eu/>

**\* Data compared to the previous version altered.**

---

— EN —