

# TOP GLOSS ADDITIVE

## CDL-07.024

### Characteristics:

Top Gloss Additive is recommended for use instead of thinner for acrylic products, it works as gloss stabilizer while also improving application properties. The product guarantees a very safe and easy application of two-component acrylic paints. It provides a very good flow, with no tendency to sag and reduces the likelihood of "gassing", even with very thick layers of paint. The coating after drying has an excellent initial gloss and hardness. Top Gloss Additive eliminates frequently found in particular in MS and HS clear coats, reduction of gloss after the curing and cooling of the surface.

### How to use:

The recommended amount of TOP Gloss Additive for clear coats:

Clear coats VOC/P, VOC/C, VOC/S: from 5% to 8% by volume

Clear coats VOC/K, VOC/E: from 5% to 6% by volume

Clear coat HS Anti Scratch: 7% by volume

Clear coats MS/P, MS/J, MS/E: 5% by volume

### Technical data:

Top Gloss Additive **CDL-07.024:**

Shelf-life: 24 months    Density: 0,85-0,86 g/cm<sup>3</sup>    Colour: colourless



### Application

Top Gloss Additive is ready for use.

Recommended use:

Clear coats VOC/P, VOC/C, VOC/S: from 5% to 8% by vol.

Clear coats VOC/K, VOC/E: from 5% to 6% by vol.

Clear coat HS: 7% by vol.

Clear coats MS: 5% by vol.