

# MULTI PLASTIC PUTTY

## CSX-01.038

### Characteristics

Highly elastic multifunctional putty designed especially for application on plastic substrates including polypropylene. Easy application and modelling. It can be used as fill and as fine putty. Provides pore-free, easy to sand coating. Adheres also to metal substrates, including steel, galvanized steel and aluminium, as well as to polyester surfaces.

### Application

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 3 - 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

**Note:** Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

### Technical data

**VOC content:** 2004/42/II B(b)(250) < 250 g/l

Shelf life: 9 months

Density: 2 – 2,1 g/cm<sup>3</sup>

Colour: dark grey



#### Cleaning



#### Hardener addition

|              |       |
|--------------|-------|
| Putty        | 100 g |
| BPO Hardener | 2-3 g |



#### Body filling

3 - 5 min.



#### Drying time

20 - 30 min



#### Hand sanding / dry

P150 - P320



#### Machine sanding / dry

P150 - P320



#### Store in cold place

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, fax +48 91 41 65 487  
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN  
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186