

MULTI LIGHT PUTTY

CSX-01.044

Characteristics

Multifunctional lightweight putty. Its creamy consistency, combined with thixotropic properties, enables safe and easy application on both horizontal and vertical surfaces. This putty is designed to apply in thick and thin layers. It does not load much weight on repairing surface due to reduced density. Soft modelling and easy sanding allow to create a very smooth finish without pores. It may be applied on steel, galvanized steel, aluminium and polyester substrates.

Application

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 5 - 7 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note: Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

Technical data

VOC content: 2004/42/II B(b)(250) < 250 g/l

Shelf life: 12 months

Density: 1,2 – 1,3 g/cm³

Colour: white



Cleaning



Hardener addition

Putty	100 g
BPO Hardener	2-3 g



Body filling

5 - 7 min.



Drying time

20 - 30 min.



Hand sanding / dry

P120 - P320



Machine sanding / dry

P120 - P320



Store in cold place

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL , tel. +48 91 41 65 440, fax +48 91 41 65 487
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186