

1K NC MULTI FILLER PASTE

CSX-01.053

v.02-12.2018

CHARACTERISTICS:

1K NC Multi Filler Paste is a one component, ready to use product, based on nitrocellulose resins. Designed for spot repair work to fill small imperfections such as scratches, pinholes and stone chip damages. Easy to apply, dries quickly in thin layers. This product creates smooth coating with minimal shrinkage and very good flexibility. It can be applied over polyester putties and acrylic primers. Suitable also for metal surfaces, including steel, aluminium and zinc-coated surfaces.

APPLICATION:

Prior to application, the surface must be cleaned, dried, degreased and matted with abrasives. Apply the filler paste in very thin layers at 20°C and allow it to dry for 15 - 30 minutes between coats. Total film thickness should not exceed 70 - 80 µm.

NOTE:

Keep tightly closed in dry, cold place. Avoid high temperature during storage and application.

TECHNICAL DATA

VOC 2004/42/IIIB(c)(540) max. 540 g/l

Shelf life: 12 months

Density: 1.67 – 1.69 g/cm³

Colour: light grey



Cleaning



Drying time

30 - 50 min (20°C) depending on the thickness



Hand sanding / dry

P240 - P400



Machine sanding / dry

P240 - P400



Store in cold place

Chemical Alliance Polska Sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, info@cap.pl, www.cap.pl

NIP 781 16 87 419, REGON 634159570, Kapitał Zakładowy 2.000.000,00 PLN

Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186, Certyfikat ISO 9001/ ISO 14001/ PN-N 18001