

NEXT GEN LIGHT MULTI PUTTY

CSX-01.023

Characteristics:

Ultra lightweight polyester putty, characterized by good adhesion to different surfaces; metal, aluminium, galvanized, wood and polyester laminates. Very soft and easy to sand, the density is 45 % lower than traditional putty. For filling in deep uneven areas and dents on motor vehicle bodywork in the area of cars, lorries, buses and railway vehicles.

Application:

The surface must be cleaned, dry, degreased and matted. Thoroughly mix putty and 2-3% of hardener BPO by weight. Apply within 8 - 10 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note: Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.

Technical data:

VOC content: 2004/42/II B(b)(250) <250

Shelf-life: 12 months Density: 0,96 - 0,97 g/cm³ Colour: beige



Cleaning



Hardener addition

Putty	100 g
BPO Hardener	2-3 g



Body filling

8 - 10 min.



Drying time

16 - 30 min.



Hand sanding / dry

P150 - P320



Machine sanding / dry

P150 - P320



Store in cold place

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, fax +48 91 41 65 487
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186