

MULTI PLUS PUTTY

CSX-01.036 (yellow)

Characteristics:

Multi Plus Putty is multifunctional polyester putty, designed for steel, aluminium, galvanized grounds and polyester laminates. Due to its excellent thixotropy it has very good shaping properties in any required thickness. It can also be used as a finishing putty, leaving smooth surface without pores.

For filling unevennesses especially on aluminium and galvanized surfaces. Destined for manual / machine treatment with sanding dry materials. For very large unevennesses putty should be applied in several layers. Does not fill sandpaper while grinding.

Application:

The surface must be cleaned, dry, degreased and matted. Thoroughly mix putty and 2-3% of hardener BPO by weight. Apply within 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note: Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.

Technical data:

VOC content: 2004/42/II(b)(250) <250

Multi Plus Putty CSX-01.036 (yellow):

Shelf-life: 12 months

Density: 1,84 - 1,86 g/cm³

Colour: yellow

Multi Plus Putty CSX-01.047 (white):

Shelf-life: 12 months

Density: 1,8 - 1,9 g/cm³

Colour: white



Cleaning



Hardener addition

Putty	100 g
BPO Hardener	2-3 g



Body filling

3 - 5 min.



Drying time

20 min.



Hand sanding / dry

P120 - P320



Machine sanding / dry

P120 - P320



Store in cold place

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, fax +48 91 41 65 487
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186