

CARBO MULTI LIGHT PUTTY

CSX-01.040

Characteristics

Multifunctional lightweight putty reinforced with carbon fibers. It shows excellent mechanical properties and is a great choice for reparation of car parts exposed to enormous tension. Suitable also for application on large surfaces due to low density. This putty provides high filling capacity with minimum weight. It may be applied in thin and thick layers giving a very smooth coating. Adhesion to all metal surfaces, including steel, galvanized steel, aluminium and polyester surfaces.

Application

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 3 - 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note: Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

Technical data

VOC content: 2004/42/II(b)(250) < 250 g/l

Shelf life: 12 months

Density: 1,2 – 1,35 g/cm³

Colour: graphite



Cleaning



Hardener addition

Putty	100 g
BPO Hardener	2-3 g



Body filling

3 - 5 min.



Drying time

20 - 30 min



Hand sanding / dry

P150 - P320



Machine sanding / dry

P150 - P320



Store in cold place

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, fax +48 91 41 65 487
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186