

# MULTI PUTTY NST

## CSX-01.054



v.02-07.2019

### CHARACTERISTICS:

Multi Putty NST is styrene-free, user friendly product. Characterized by creamy texture and easy sanding without clogging sandpaper. It creates a perfect pinhole-free coating with good flexibility. Suitable for filling up dents and other imperfections on all sheet metal surfaces, as well on zinc-coated and aluminium.

### APPLICATION:

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 4 - 6 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

**NOTE:** Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

### TECHNICAL DATA:

**VOC 2004/42/II(b)(250) max. 250 g/l**

Shelf life: 12 months

Density: 1.75 - 1.77 g/cm<sup>3</sup>

Colour: light green



**Cleaning**



**Hardener addition**

Putty 100 g

BPO Hardener 2 - 3 g



**Body filling**

4 - 6 min



**Drying time**

30 min



**Sanding / dry**

P120 – P280



**Store in cold place**

**Chemical Alliance Polska Sp. z o.o.**

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, info@cap.pl, www.cap.pl

NIP 781 16 87 419, REGON 634159570, Kapitał Zakładowy 2.000.000,00 PLN

Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186, Certyfikat ISO 9001/ ISO 14001/ PN-N 18001