

# MULTI SOFT PUTTY

## CSX-01.057

### Characteristics:

Multi-purpose, soft putty with filling properties. It contains fine-grained and lightweight fillers. Characterized by creamy consistency, this putty is very easy to apply and model, even on vertical surfaces. It may be applied in both thin and thick layers. It creates an elastic and very smooth, pore-free coating. This putty is soft to sand and doesn't clog the sandpaper. It adheres to steel, aluminium, zinc-coated and polyester surfaces.

### Application:

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 4 - 6 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

**Note:** Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

### Technical data:

VOC 2004/42/IIIB(b)(250) max. 250 g/l

Putty CSX-01.057:

Shelf-life: 12 months

Density: 1,6 – 1,7 g/cm<sup>3</sup>

Colour: dark yellow



**Cleaning**



**Hardener addition**

Putty	100 g
BPO Hardener	2-3 g



**Body filling**

4 - 6 min



**Drying time**

20 - 30 min



**Hand sanding / dry**

P150 - P320



**Machine sanding / dry**

P150 - P320



**Store in cold place**

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, fax +48 91 41 65 487  
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN  
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186