

# UNIVERSAL SOFT GREY PUTTY

## CSX-01.066

### Characteristics:

Multifunctional two-component polyester putty combining the excellent spreadability, compactness and easy to sand. Specially formulated to achieve the highest finish levels on steel, zinc coated and aluminium surfaces as well as polyester laminates. It may be applied in both thin and thick layers.

### Application:

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2% of BPO hardener. Apply within 4-5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time

**Note:** Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

### Technical data:

**VOC 2004/42/IIIB(b)(250) max. 250g/l**

Shelf-life: 12 months

Density: 1.56 – 1.58 g/cm<sup>3</sup>

Colour: grey



### Cleaning



### Hardener addition

Putty	100 g
BPO Hardener	2 g



### Body filling

4 - 5 min



### Drying time

20 - 25 min



### Hand sanding / dry

P120 - P280



### Machine sanding / dry

P120 - P280



### Store in cold place

Chemical Alliance Polska sp. z o.o.

ul. Prosta 23, Łozienica, 72-100 Goleniów, PL, tel. +48 91 41 65 440, fax +48 91 41 65 487  
NIP 781 16 87 419 REGON 6341159570, Kapitał Zakładowy 2.000.000,00 PLN  
Sąd Rejonowy w Szczecinie XVII Wydział Gospodarczy KRS 0000003186